

760 liter tank i Syrafast 316



150 000 SEK /st exkl moms

Additional information: Feet with load cells (see photos)

Volumetric volume (L): 760 L

Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar



Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 30

Agitator: yes

Number of revolutions: 224

Power: 0,75

Internal diameter tank: 890 mm

Outer diameter tank: 1.070 mm

Cylinder height: 930 mm

Total height of tank: 2.200 mm

SKU: 704560



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: insulated

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Feet with load cells (see photos); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 760

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 930 mm

Invändig diameter: 890 mm

Total höjd: 2.200 mm

Ytterdiameter: 1.070 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 224

Mer

Isolerad: Ja