

80 liter tank i Syrafast 316



88,000,00 kr /st exkl moms

Additional information: Pharmacy; 1 screwed fitting enlarges the actual outlet from DN 20 to DN 50 DIN 11851 (see photos)

Volumetric volume (L): 80 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 2 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN20 DIN 11851

Agitator: yes

Number of revolutions: 310 - 1865

Power: 1,35

Internal diameter tank: 490 mm

Outer diameter tank: 540 mm

Total height of tank: 1.800 mm

SKU: 482044

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; 1 screwed fitting enlarges the actual outlet from DN 20 to DN 50
DIN 11851 (see photos); we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 80

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 490 mm

Total höjd: 1.800 mm

Ytterdiameter: 540 mm

Omrörare

Kraft (kW): 1,35

Varvtal: 310 - 1865

Mer

Värmeväxlare: RVS 304

Isolerad: Nej