80 liter tank i Syrafast 316



89 000 SEK /st exkl moms

Additional information: Pharmacy; 1 screwed fitting enlarges the actual outlet from DN 20 to DN 50 DIN 11851 (see photos)
Volumetric volume (L): 80 L
Pressure in tank: pressure
Max. pressure (Bar): 3 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no

Mobile tank: no
Total discharge: yes
Volume: 20 L
Max Overpressure: 2 Bar
Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN20 DIN 11851
Agitator: yes
Number of revolutions: 310 - 1865

Power: 1,35
Internal diameter tank: 490 mm
Outer diameter tank: 540 mm
Total height of tank: 1.800 mm

SKU: 482044

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Pharmacy; 1 screwed fitting enlarges the actual outlet from DN 20 to DN 50 DIN 11851 (see photos); we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 80

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Invändig diameter: 490 mm
Total höjd: 1.800 mm
Ytterdiameter: 540 mm

Omrörare
Kraft (kW): 1,35
Varvtal: 310 – 1865

Mer
Värmeväxlare: RVS 304
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se