80 liter tank i Syrafast 316



244 000 SEK /st exkl moms

Additional information: Vessel was only tested for validation purposes; technical documentation was ordered from the manufacturer, but has not yet arrived; plastic rollers for the feet were unscrewed for shipping, but are enclosed loose (see photos)
Volumetric volume (L): 80 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 95 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 16 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 95 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25
Agitator: yes
Number of revolutions: 125 - 800

Power: 0,09
Cylinder: 3,40 mm
Bottom: 3 mm
Internal diameter tank: 357 mm
Outer diameter tank: 457 mm

Total height of tank: 1.650 mm

SKU: 483755

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 95 °C
Mobil tank: Nej
Övrig information: Vessel was only used for validation and never went into service; technical documentation was ordered from the manufacturer but has not yet arrived; plastic casters on the feet were unscrewed for
Övrig information2: shipping but are included loose (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Yes
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 80

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Invändig diameter: 357 mm
Total höjd: 1.650 mm
Ytterdiameter: 457 mm

Omrörare
Kraft (kW): 0,09
Varvtal: 125 – 800

Tjocklek på tank
Botten: 3 mm
Cylinder: 3,40 mm

Mer
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se