

800 liter tank i Rostfritt 304



15 000 SEK /st exkl moms

Article type: second-hand transport tank

Additional information: The tanks have some dents; look closely at the photos; used for various egg products. Not all tanks have nameplates.

Volumetric volume (L): 800 L

Pressure in tank: pressure

Max. pressure (Bar): 1 Bar

Min. pressure (Bar): -0,15 Bar

Max. temperature (°C): 50 °C

Min. temperature (°C): 5 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 stackable frame

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: yes

Distance from outlet to ground: 200 mm

Outer diameter tank: 1.030 mm

Cylinder height: 880 mm

Total height of tank: 1.560 mm

Empty weight tank: 117

SKU: 570005

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 50 °C

Min. arbetstemperatur: 5 °C

Mobil tank: Nej

Övrig information: The tanks have some dents; look closely at the photos; used for various egg products. Not all tanks have nameplates.

Omrörare: Nej

Övertryck: 1 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Undertryck (vakuum): -0,15 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 800



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851
Utloppsventil: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 880 mm
Mått utlopp till marken: 200 mm
Total höjd: 1.560 mm
Ytterdiameter: 1.030 mm

Mer

Isolerad: Nej
Vikt: 117