800 liter tank i Rostfritt 304



14 000 SEK /st exkl moms

Article type: second-hand transport tank
Additional information: The tanks have some dents; look closely at the photos; used for various egg products. Not all tanks have nameplates.
Volumetric volume (L): 800 L
Pressure in tank: pressure
Max. pressure (Bar): 1 Bar

Min. pressure (Bar): -0,15 Bar
Max. temperature (°C): 130 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: dished

Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 stackable frame
Manway(s): RVS 304

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm
Tank outlet: inside Ø 50 mm

Outlet type: DIN11851
Total outlet valve: yes
Distance from outlet to ground: 200 mm
Outer diameter tank: 1.030 mm
Cylinder height: 860 mm

Total height of tank: 1.530 mm
Empty weight tank: 180

SKU: 569825

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 130 °C
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: The tanks have some dents; look closely at the photos; used for various egg products. Not all tanks have nameplates.
Omrörare: Nej
Övertryck: 1 Bar
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Undertryck (vakuum): -0,15 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 800

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851
Utloppsventil: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 860 mm
Mått utlopp till marken: 200 mm
Total höjd: 1.530 mm
Ytterdiameter: 1.030 mm

Mer

Isolerad: Nej
Vikt: 180