800 liter tank i Syrafast 316



18 000 SEK /st exkl moms

Additional information: Diameter manhole approx. 385 mm; slight differences in design; 1 container with a type plate (difficult to read) and with outlet Diameter tube inside approx. 35 mm (this container has a smaller dent in the transition cylinder/bottom)
Volumetric volume (L): 800 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: 48
Internal diameter tank: 1.190 mm
Cylinder height: 550 mm
Total height of tank: 1.680 mm

SKU: 476566

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Pharmacy; Diameter of manhole approx. 385 mm; slight differences in design; 1 container with a type plate (hard to read) and with outlet, pipe diameter inside approx. 35 mm (this container has a
Övrig information2: smaller dent in the cylinder/lower bottom transition)
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 800

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 550 mm
Invändig diameter: 1.190 mm
Total höjd: 1.680 mm

Mer

Isolerad: Nej

Rodervägen 57
891 78 Bonässund
info@processoverskott.se