8000 liter tank i Rostfritt 304



100 000 SEK /st exkl moms

Additional information: Minor differences in the design of the two tanks (e.g. location of the outlets); manhole diameter approx. 510 mm; a former manhole and 1 connection in the lower cylinder area were welded shut by the previous operator; 1 tank with a small dent in the iso jacket; see photos
Volumetric volume (L): 8.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN65 DIN 11851
Agitator: yes
Number of revolutions: 900
Power: 0,55
Internal diameter tank: 1.690 mm

Outer diameter tank: 1.800 mm
Cylinder height: 3.500 mm
Total height of tank: 4.550 mm

SKU: 430088

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Dairy; Minor differences in the design of the two tanks (e.g. location of the outlets); Manhole diameter approx. 510 mm; a former manhole and 1 connection in the lower cylinder area were welded shut
Övrig information2: by the previous operator; 1 tank with a smaller dent in the insulating jacket; see photos; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 8000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.500 mm
Invändig diameter: 1.690 mm
Total höjd: 4.550 mm
Ytterdiameter: 1.800 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 900

Mer
Isolerad: Ja