

8000 liter tank i Rostfritt 304



99,000,00 kr /st exkl moms

Additional information: Dairy; Minor differences in the design of the two tanks (e.g. location of the outlets); Manhole diameter approx. 510 mm; a former manhole and 1 connection in the lower cylinder area were welded shut by the previous operator; 1 tank with a smaller dent in the insulating jacket; see photos

Volumetric volume (L): 8.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN65 DIN 11851
Agitator: yes
Number of revolutions: 900
Power: 0,55
Internal diameter tank: 1.690 mm

Outer diameter tank: 1.800 mm
Cylinder height: 3.500 mm
Total height of tank: 4.550 mm

SKU: 309469

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Dairy; Minor differences in the design of the two tanks (e.g. location of the outlets); Manhole diameter approx. 510 mm; a former manhole and 1 connection in the lower cylinder area were welded shut

Övrig information2: by the previous operator; 1 tank with a smaller dent in the insulating jacket; see photos; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 8000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.500 mm

Invändig diameter: 1.690 mm

Total höjd: 4.550 mm

Ytterdiameter: 1.800 mm

Omrörare

Kraft (kW): 0,55

Varvtal: 900

Mer

Isolerad: Ja