8000 liter tank i Rostfritt 304



118 000 SEK /st exkl moms

Additional information: pipe end cut flush
Volumetric volume (L): 8.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: available
Agitator: yes
Number of revolutions: 47
Power: 0,55
Cylinder: 3,10 mm

Bottom: 2,90 mm
Internal diameter tank: 2.080 mm
Outer diameter tank: 2.200 mm
Cylinder height: 2.350 mm
Total height of tank: 3.700 mm

SKU: 564886

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: pipe end cut flush; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 8000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.350 mm
Invändig diameter: 2.080 mm
Total höjd: 3.700 mm
Ytterdiameter: 2.200 mm

Omrörare

Kraft (kW): 0,55
Varvtal: 47

Tjocklek på tank
Botten: 2,90 mm
Cylinder: 3,10 mm

Mer
Isolerad: Ja