

8000 liter tank i Rostfritt 304



82 000 SEK /st exkl moms

Additional information: Food industry; Former double jacket no longer functional; some residues of previous content

Volumetric volume (L): 8.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,40 Bar

Min. pressure (Bar): 0,20 Bar

Max. temperature (°C): 110 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Fixation points: 4 adjustable feet

Volume: 60 L

Max Overpressure: 0,40 Bar

Max onderdruk: 0,20 Bar

Max. working temperature: 110 °C

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 16

Power: 4

Internal diameter tank: 2.490 mm

Outer diameter tank: 2.650 mm

Cylinder height: 1.500 mm

Total height of tank: 4.000 mm

SKU: 267340

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 110 °C

Mobil tank: Nej

Övrig information: Food industry; Former double jacket no longer functional; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 0,40 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,20 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 8000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 2.490 mm
Total höjd: 4.000 mm
Ytterdiameter: 2.650 mm

Omrörare

Kraft (kW): 4
Varvtal: 16

Mer

Värmeväxlare: RVS 304
Isolerad: Ja