

8000 liter tank i Rostfritt 304



126,000,00 kr /st exkl moms

Additional information: chemistry; 1 tank with a dent in the cylindrical part as well as in the fan guard of the agitator motor; some residues of previous content

Volumetric volume (L): 8.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: flange DN50
Agitator: yes
Number of revolutions: 45 / 90
Power: 9.9 / 16

Cylinder: 5 mm
Bottom: 5 mm
Internal diameter tank: 1.658 mm
Cylinder height: 3.270 mm
Total height of tank: 5.950 mm

SKU: 266287

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: chemistry; 1 tank with a dent in the cylindrical part as well as in the fan guard of the agitator motor; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 8000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.270 mm

Invändig diameter: 1.658 mm

Total höjd: 5.950 mm

Omrörare

Kraft (kW): 9.9 / 16

Varvtal: 45 / 90

Tjocklek på tank

Botten: 5 mm

Cylinder: 5 mm

Mer

Isolerad: Nej