8000 liter tank i Rostfritt 304



126 000 SEK /st exkl moms

Additional information: chemistry; 1 vessel with dent in the cylinder and in the fan cover of the agitator motor; some residues of previous content
Volumetric volume (L): 8.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 100 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: flange DN50
Agitator: yes
Number of revolutions: 45 / 90
Power: 9.9 / 16

Cylinder: 5 mm
Bottom: 5 mm
Internal diameter tank: 1.658 mm
Cylinder height: 3.270 mm
Total height of tank: 5.950 mm

SKU: 390467

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: chemistry; 1 tank with a dent in the cylindrical part as well as in the fan guard of the agitator motor; some residues of previous content; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 8000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.270 mm
Invändig diameter: 1.658 mm
Total höjd: 5.950 mm

Omrörare

Kraft (kW): 9.9 / 16
Varvtal: 45 / 90

Tjocklek på tank
Botten: 5 mm
Cylinder: 5 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se