8000 liter tank i Syrafast 316



217 000 SEK /st exkl moms

Additional information: Chemistry; 4 support brackets, Fe; double jacket blasted and primed; Type plate probably not available
Volumetric volume (L): 8.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 135 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 600 L
Max. working temperature: 135 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: flange DN100
Agitator: yes
Number of revolutions: 140

Power: 30
Cylinder: 13 mm
Bottom: 10 mm
Internal diameter tank: 2.200 mm
Outer diameter tank: 2.300 mm

Cylinder height: 1.830 mm
Total height of tank: 5.100 mm

SKU: 423623

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 135 °C
Mobil tank: Nej
Övrig information: Chemistry; 4 support brackets, Fe; double jacket blasted and primed; Type plate probably not available; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 8000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.830 mm
Invändig diameter: 2.200 mm
Total höjd: 5.100 mm
Ytterdiameter: 2.300 mm

Omrörare
Kraft (kW): 30
Varvtal: 140

Tjocklek på tank
Botten: 10 mm
Cylinder: 13 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se