8000 liter tank i Syrafast 316



77 000 SEK /st exkl moms

Additional information: detergents; manhole appr. 345 x 440 mm; some residues of previous content
Volumetric volume (L): 8.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: DN65 DIN 11851
Cylinder: 2,50 mm
Bottom: 2,40 mm
Internal diameter tank: 2.000 mm
Cylinder height: 2.500 mm

Total height of tank: 3.500 mm

SKU: 393659

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: detergents; Manhole appr. 345 x 440 mm; some residues of previous content
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 8000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 2.000 mm
Total höjd: 3.500 mm

Tjocklek på tank

Botten: 2,40 mm
Cylinder: 2,50 mm

Mer
Isolerad: Nej