



8100 liter tank i Syrafast 316



item available on order

Article type: brand new storage tank - type K2-SL

Capacity: 8.100 L

Maximal density of the product: 1.200

Ra inner weld: 1,60

Finish stainless steel: 2b

Working pressure in tank: ATM - atmosferic

Design pressure of the tank: 0,05 Bar

Max. working temperature: 100 °C

Min. working temperature: -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Agitator: yes, optional



Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

with inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position manway: at the top

Manway 1: 500 mm

Spray ball: yes, optional

Max. temperature CIP: 30 °C

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851 male

Total outlet valve: yes, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 2 mm

Distance from outlet to ground: 306 mm

Outer diameter tank: 1.874 mm

Cylinder height: 2.750 mm

Feet height: 630 mm

Total height of tank: 3.733 mm

Empty weight tank: 412

SKU: 10103



Additional Information

Volym i liter	8100
Nyttillverkad/Begagnad	Nyttillverkad
Livsmedelsklassad	Ja
Modell	Vertikal
Material	Syrafast 316
Omrörare	Nej
Uppvärmning/kylning	Nej
Isolerad	Nej