

820 liter tank i Syrafast 316



63,000 SEK /st exkl moms

Additional information: 1 DN 200 hand hole in the upper bottom; 1 welded stainless steel insulating collar around the outside of the vessel; some residues of previous content

Volumetric volume (L): 820 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 160 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 52 L

Max Overpressure: 6 Bar

Max. working temperature: 160 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Internal diameter tank: 780 mm

Outer diameter tank: 830 mm

Cylinder height: 1.400 mm

Total height of tank: 3.000 mm

SKU: 566195

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 160 °C

Mobil tank: Nej

Övrig information: 1 DN 200 hand hole in the upper bottom; 1 welded stainless steel insulating collar around the outside of the vessel; some residues of previous content

Omrörare: Nej

Övertryck: 0,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 820

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.400 mm

Invändig diameter: 780 mm

Total höjd: 3.000 mm

Ytterdiameter: 830 mm

Mer

Isolerad: Nej
