8500 liter tank i Rostfritt 304



71 000 SEK /st exkl moms

Article type: second-hand storage tank
Additional information: Tank comes from the coffee industry, still residue from the previous product in the tank.
Volumetric volume (L): 8.500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: strong conical
Total discharge: yes
Fixation points: 3 non adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Valve: RVS 304

Gasket shut-off valve (mat): unknown
Fixation point(s): RVS 304
Suitable for food industry: no
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 50 mm
Outlet type: DIN11851
Total outlet valve: yes
Insulation body: yes
Insulation bottom/sides: yes

finish of the outer jacket: welded
Insulation thickness: 50
Internal diameter tank: 1.700 mm
Distance from outlet to ground: 500 mm
Outer diameter tank: 1.850 mm

Cylinder height: 3.540 mm
Total height of tank: 5.850 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Empty weight tank: 900

SKU: 489513

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Tank comes from the coffee industry, still residue from the previous product in the tank.
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: strong conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 8500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851
Utloppsventil: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 3.540 mm
Invändig diameter: 1.700 mm
Mått utlopp till marken: 500 mm
Total höjd: 5.850 mm
Ytterdiameter: 1.850 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 50
Isolerad: Ja
Vikt: 900