

8609 liter tank i Syrafast 316



185,000,00 kr /st exkl moms

Additional information: Chemistry; Support ring, Fe; Manhole diameter appr. 480 mm; vessel with corrosion on the inside (see photos); Total height including agitator gear (without gear approx. 3400 mm); ; motor is missing; manhole cover is missing

Volumetric volume (L): 8.609 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 313 L

Max Overpressure: 20 Bar

Max onderdruk: 1 Bar

Max. working temperature: 220 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 100

Agitator: yes

Number of revolutions: 52 / 104

Top: 14 mm

Cylinder: 8 mm

Bottom: 10 mm

Internal diameter tank: 2.000 mm

Cylinder height: 2.190 mm

Total height of tank: 4.950 mm

SKU: 299662

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Support ring, Fe; Manhole diameter appr. 480 mm; vessel with corrosion on the inside (see photos); Total height including agitator gear (without gear approx. 3400 mm); ; motor is

Övrig information2: missing;manhole cover is missing

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 8609

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.190 mm

Invändig diameter: 2.000 mm

Total höjd: 4.950 mm

Omrörare

Varvtal: 52 / 104

Tjocklek på tank

Botten: 10 mm

Cylinder: 8 mm

Topp: 14 mm

Mer

Isolerad: Nej