

865 liter tank i Syrafast 316



74 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 3 support brackets, stainless steel; 1 hand hole DN 250 in the upper bottom; flanged outlet fitting reduces the outlet to approx. 30 mm (components of this fitting that do not come into contact with the product are made of Fe (see photos)); handhole cover is missing

Volumetric volume (L): 865 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 11 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 30

Top: 5,20 mm

Cylinder: 5 mm

Bottom: 4,30 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.230 mm

Cylinder height: 810 mm

Total height of tank: 1.800 mm

Empty weight tank: 325

SKU: 288506

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 3 support brackets, stainless steel; 1 hand hole DN 250 in the upper bottom; flanged outlet fitting reduces the outlet to approx. 30 mm

(components of this fitting that do

Övrig information2: not come into contact with the product are made of Fe (see photos)) ;

handhole cover is missing; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 865

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 810 mm

Invändig diameter: 1.000 mm

Total höjd: 1.800 mm

Ytterdiameter: 1.230 mm

Tjocklek på tank

Botten: 4,30 mm

Cylinder: 5 mm

Topp: 5,20 mm

Mer

Isolerad: Ja

Vikt: 325