

## 865 liter tank i Syrafast 316



**75,000,00 kr /st exkl moms**

**Additional information:** Pharmaceutical chemistry; 3 support brackets, stainless steel; 1 hand hole DN 250 in the upper bottom; flanged outlet fitting reduces the outlet to approx. 30 mm (components of this fitting that do not come into contact with the product are made of Fe (see photos)); handhole cover is missing

**Volumetric volume (L):** 865 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 2 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 11 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 30

**Top:** 5,20 mm

**Cylinder:** 5 mm

**Bottom:** 4,30 mm

**Internal diameter tank:** 1.000 mm

**Outer diameter tank:** 1.230 mm

**Cylinder height:** 810 mm

**Total height of tank:** 1.800 mm

**Empty weight tank:** 325

**SKU:** 288506

---

Mer information

---