885 liter tank i Syrafast 316



162 000 SEK /st exkl moms

Additional information: At the previous operator, the vessels were suspended in a ring with load cells, which was embedded in the floor (1 ring each is included in the scope of delivery; see photos); outer diameter in the ring approx. 1,540 mm; insulating jacket made of material 1.0425
Volumetric volume (L): 885 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 35 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 140 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 55

Agitator: yes
Number of revolutions: 416
Power: 0,55
Cylinder: 6 mm
Bottom: 4,50 mm

Internal diameter tank: 1.000 mm
Cylinder height: 864 mm

SKU: 443390-1

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: Pharmacy; The previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery; see photos); Outer diameter in the ring
Övrig information2: approx. 1,540 mm; insulating jacket made of material 1.0425; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 885

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 864 mm
Invändig diameter: 1.000 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 416

Tjocklek på tank
Botten: 4,50 mm
Cylinder: 6 mm

Mer
Isolerad: Ja