

## 8890 liter tank i Syrafast 316



**549,000,00 kr /st exkl moms**

**Additional information:** Tank was manufactured for a global pharmaceutical company but was never put into operation; Diameter of outlet (fitting) approx. 44 mm

**Volumetric volume (L):** 8.890 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 143 L

**Max Overpressure:** 10 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Top:** 12,50 mm

**Cylinder:** 7,60 mm

**Bottom:** 9,50 mm

**Internal diameter tank:** 2.200 mm

**Outer diameter tank:** 2.400 mm

**Total height of tank:** 4.000 mm

**SKU:** 441419

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Tank was manufactured for a global pharmaceutical company but was never put into operation; Diameter of outlet (fitting) approx. 44 mm; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 8890

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## Dimensioner av tank

Invändig diameter: 2.200 mm

Total höjd: 4.000 mm

Ytterdiameter: 2.400 mm

## Tjocklek på tank

Botten: 9,50 mm

Cylinder: 7,60 mm

Topp: 12,50 mm

## Mer

Isolerad: Ja