

90 liter tank i Syrafast 316



52,000,00 kr /st exkl moms

Additional information: Liquid soap; tank is the smaller, right tank in the photo of the previous operator; tank was part of a process plant (the larger tank in the photo is also available under order number 9786 (subject to sale elsewhere)

Volumetric volume (L): 90 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Top type: open
Total discharge: yes
Max Overpressure: 6 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Outlet of tank: 38
Agitator: yes
Number of revolutions: 34
Power: 1,10
Cylinder: 5 mm

Bottom: 4 mm
Internal diameter tank: 500 mm
Outer diameter tank: 650 mm
Cylinder height: 820 mm
Total height of tank: 2.800 mm

SKU: 479148

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Liquid soap; tank is the smaller, right tank in the photo of the previous operator; tank was part of a process plant (the larger tank in the photo is also available under order number 9786 (subject

Övrig information2: to sale elsewhere); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 90

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 820 mm
Invändig diameter: 500 mm
Total höjd: 2.800 mm
Ytterdiameter: 650 mm

Omrörare

Kraft (kW): 1,10
Varvtal: 34

Tjocklek på tank

Botten: 4 mm
Cylinder: 5 mm

Mer

Isolerad: Ja