

900 liter tank i Syrafast 316



202 000 SEK /st exkl moms

Additional information: Pharmacy; The two existing drawings are conversion drawings (vessel was converted by DIESEL in 2000); 3 foot extensions with load cells are included in the scope of delivery

Volumetric volume (L): 900 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 58 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 25

Agitator: yes

Power: 0,75

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.150 mm

Total height of tank: 2.250 mm

SKU: 482562

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; The two existing drawings are conversion drawings (vessel was converted by DIESSEL in 2000); 3 foot extensions with load cells are included in the scope of delivery; we can't give any

Övrig information2: guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 900

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 1.000 mm

Total höjd: 2.250 mm

Ytterdiameter: 1.150 mm

Omrörare

Kraft (kW): 0,75

Mer

Isolerad: Ja