

9000 liter tank i Rostfritt 304



153 000 SEK /st exkl moms

Additional information: Sterile tank in a dairy; Double jacket with trickle ring - only suitable for cooling; 1 former connection in the upper bottom welded shut; connections partially deflected; weld seam of the double jacket has partially come loose in the upper cylinder area (see photos); pipe end cut flush

Volumetric volume (L): 9.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 80

Top: 6 mm

Cylinder: 8 mm

Bottom: 8,40 mm

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.044 mm

Cylinder height: 2.500 mm

Total height of tank: 4.350 mm

SKU: 308485

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Sterile tank in a dairy; Double jacket with trickle ring – only suitable for cooling; 1 former connection welded shut in the upper bottom; connections partially cut off; weld seam of the double

Övrig information2: jacket has partially come loose in the upper cylinder area (see photos); pipe end cut flush

Omrörare: Nej

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 9000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 2.000 mm
Total höjd: 4.350 mm
Ytterdiameter: 2.044 mm

Tjocklek på tank

Botten: 8,40 mm
Cylinder: 8 mm
Topp: 6 mm

Mer

Isolerad: Nej