

9000 liter tank i Rostfritt 304



192,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: half coil for heating on the cylinder and on the bottom and a tube heat exchanger in the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 13.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 loadcells

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the complet cilinder

Type HE: spiral pipes inside the tank

Type of HE on the bottom: half pipe welded onto the outside of the innertank

Heat exchanger bottom connected with cylinder: yes

Connection of the bottom to the cylinder: binnan isolatie

Heat exchanger: RVS 304

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Hinged lid: yes

Tank outlet: inside Ø 60 mm

Agitator: yes

Agitator type: 4 blade impeller

Position engine: at the top
Number of revolutions: 25
Power: 4
Voltage: 380 V - three-phase
Internal diameter tank: 2.200 mm

Distance from outlet to ground: 220 mm
Outer diameter tank: 2.300 mm
Cylinder height: 2.500 mm
Total height of tank: 3.900 mm
Empty weight tank: 1.200

SKU: 485897

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: half coil for heating on the cylinder and on the bottom and a tube heat exchanger in the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Övrig information2: agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 13500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Tankutlopp: inside Ø 60 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Ytterbeklädnad: RVS 304L

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 2.200 mm
Mått utlopp till marken: 220 mm
Total höjd: 3.900 mm
Ytterdiameter: 2.300 mm

Värmeväxlare

Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank
Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank

Omrörare

Kraft (kW): 4
Position motor: at the top
Typ av omrörare: 4 blade impeller
Varvtal: 25
Spänning (Volt): 380 V – three-phase

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

Mer

Värmeväxlare: RVS 304
Isolerad: Ja
Vikt: 1.200