

## 9000 liter tank i Rostfritt 304



**190 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** half coil for heating on the cylinder and on the bottom and a tube heat exchanger in the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

**Volumetric volume (L):** 13.500 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** dished

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 4 loadcells

**Type of HE on the cylinder:** half pipe welded onto the outside of the innertank

**Position HE:** the complet cilinder

**Type HE:** spiral pipes inside the tank

**Type of HE on the bottom:** half pipe welded onto the outside of the innertank

**Heat exchanger bottom connected with cylinder:** yes

**Connection of the bottom to the cylinder:** binnan isolatie

**Heat exchanger:** RVS 304

**Insulation material:** rockwool

**Outer jacket (ornamental wall):** RVS 304L

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Wet parts agitator(s):** SS AISI 304 (V2A)

**Suitable for food industry:** no

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** headside

**Hinged lid:** yes

**Tank outlet:** inside Ø 60 mm

**Agitator:** yes

**Agitator type:** 4 blade impeller

**Position engine:** at the top  
**Number of revolutions:** 25  
**Power:** 4  
**Voltage:** 380 V - three-phase  
**Internal diameter tank:** 2.200 mm

**Distance from outlet to ground:** 220 mm  
**Outer diameter tank:** 2.300 mm  
**Cylinder height:** 2.500 mm  
**Total height of tank:** 3.900 mm  
**Empty weight tank:** 1.200

**SKU:** 485897

## Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: half coil for heating on the cylinder and on the bottom and a tube heat exchanger in the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Övrig information2: agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 13500

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Tankutlopp: inside Ø 60 mm

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Ytterbeklädnad: RVS 304L

## Dimensioner av tank

Cylinderhöjd: 2.500 mm  
Invändig diameter: 2.200 mm  
Mått utlopp till marken: 220 mm  
Total höjd: 3.900 mm  
Ytterdiameter: 2.300 mm

## Värmeväxlare

Position värmeväxlare: the complet cilinder  
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank  
Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank

## Omrörare

Kraft (kW): 4  
Position motor: at the top  
Typ av omrörare: 4 blade impeller  
Varvtal: 25  
Spänning (Volt): 380 V – three-phase

## Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

## Mer

Värmeväxlare: RVS 304  
Isolerad: Ja  
Vikt: 1.200