

9140 liter tank i Rostfritt 304



135 000 SEK /st exkl moms

Additional information: Processing of wool fat; Maximum operating pressure heating coil 35 bar; 3 claws, Fe; manhole diameter approx. 490 mm; several external parts made of Fe, e.g. manhole cover flange and insulating rings around the cylinder; pipe end cut flush

Volumetric volume (L): 9.140 L

Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 219 L

Max. working temperature: 242 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 160

Top: 6,30 mm

Cylinder: 6,30 mm

Bottom: 6,10 mm

Internal diameter tank: 1.990 mm

Cylinder height: 2.400 mm

Total height of tank: 3.750 mm

SKU: 304415

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Processing of wool fat; Maximum operating pressure heating coil 35 bar; 3 support brackets, Fe; Manhole diameter approx. 490 mm; several external parts made of Fe, e.g. B. manhole cover flange and

Övrig information2: insulating rings around the cylinder; pipe end cut flush

Omrörare: Nej

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 9140

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.400 mm

Invändig diameter: 1.990 mm

Total höjd: 3.750 mm

Tjocklek på tank

Botten: 6,10 mm

Cylinder: 6,30 mm

Topp: 6,30 mm

Mer

Isolerad: Nej