

## 9140 liter tank i Rostfritt 304



**136 000 SEK /st exkl moms**

**Additional information:** Processing of wool fat; Maximum operating pressure heating coil 35 bar; 3 claws, Fe; manhole diameter approx. 490 mm; several external parts made of Fe, e.g. manhole cover flange and insulating rings around the cylinder; pipe end cut flush

**Volumetric volume (L):** 9.140 L

**Pressure in tank:** vacuum

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 219 L

**Max. working temperature:** 242 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** cylinder

**Outlet of tank:** 160

**Top:** 6,30 mm

**Cylinder:** 6,30 mm

**Bottom:** 6,10 mm

**Internal diameter tank:** 1.990 mm

**Cylinder height:** 2.400 mm

**Total height of tank:** 3.750 mm

**SKU:** 304415

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Processing of wool fat; Maximum operating pressure heating coil 35 bar; 3 support brackets, Fe; Manhole diameter approx. 490 mm; several external parts made of Fe, e.g. B. manhole cover flange and

Övrig information2: insulating rings around the cylinder; pipe end cut flush

Omrörare: Nej

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 9140

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

### Dimensioner av tank

Cylinderhöjd: 2.400 mm

Invändig diameter: 1.990 mm

Total höjd: 3.750 mm

**Tjocklek på tank**

Botten: 6,10 mm

Cylinder: 6,30 mm

Topp: 6,30 mm

**Mer**

Isolerad: Nej