

930 liter tank i Syrafast 316



99 000 SEK /st exkl moms

Additional information: pharmacy; 1 vessel with extensive documentation (the second vessel only with test certificates and copy of the certificate of conformity); one vessel with dent in the insulating jacket (see pictures); filling pipe inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet

Volumetric volume (L): 930 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 90 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN25 DIN 11851

Internal diameter tank: 988 mm

Cylinder height: 900 mm

Total height of tank: 2.250 mm

SKU: 482179

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: pharmacy; 1 vessel with extensive documentation (the second vessel only with test certificates and copy of the certificate of conformity); one vessel with dent in the insulating jacket (see

Övrig information2: pictures); filling pipe inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 930

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 900 mm

Invändig diameter: 988 mm

Total höjd: 2.250 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja