

## 930 liter tank i Syrafast 316



**99,000,00 kr /st exkl moms**

**Additional information:** pharmacy; 1 vessel with extensive documentation (the second vessel only with test certificates and copy of the certificate of conformity); one vessel with dent in the insulating jacket (see pictures); filling pipe inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet

**Volumetric volume (L):** 930 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 130 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 90 L

**Max Overpressure:** 3 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 130 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** DN25 DIN 11851

**Internal diameter tank:** 988 mm

**Cylinder height:** 900 mm

**Total height of tank:** 2.250 mm

**SKU:** 482179

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: pharmacy; 1 vessel with extensive documentation (the second vessel only with test certificates and copy of the certificate of conformity); one vessel with dent in the insulating jacket (see

Övrig information2: pictures); filling pipe inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 930

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 900 mm

Invändig diameter: 988 mm

Total höjd: 2.250 mm

## Mer

Värmeväxlare: RVS 304

Isolerad: Ja