930 liter tank i Syrafast 316



100 000 SEK /st exkl moms

Additional information: pharmacy; 1 vessel with extensive documentation (the second vessel only with test certificates and copy of the certificate of conformity); one vessel with dent in the insulating jacket (see pictures); filling pipe inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet
Volumetric volume (L): 930 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 90 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 130 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN25 DIN 11851
Internal diameter tank: 988 mm
Cylinder height: 900 mm
Total height of tank: 2.250 mm

SKU: 482179

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: pharmacy; 1 vessel with extensive documentation (the second vessel only with test certificates and copy of the certificate of conformity); one vessel with dent in the insulating jacket (see
Övrig information2: pictures); filling pipe inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 930

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 900 mm
Invändig diameter: 988 mm
Total höjd: 2.250 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se