

## 950 liter tank i Syrafast 316



**52,000,00 kr /st exkl moms**

**Additional information:** bitumen; frame with platform made of mild steel belongs to the delivery; some residues of previous content; dents at the insulation jacket

**Volumetric volume (L):** 950 L

**Pressure in tank:** ATM - atmospheric

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Outlet of tank:** flange DN50

**Agitator:** yes

**Number of revolutions:** 20 - 120

**Power:** 1,50

**Internal diameter tank:** 1.000 mm

**Outer diameter tank:** 1.250 mm

**Cylinder height:** 1.120 mm

**Total height of tank:** 3.350 mm

**SKU:** 269026

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: bitumen; frame with platform made of mild steel belongs to the delivery; some residues of previous content;dents at the insulation jacket; we can't give any guarantees about the heating/cooling

Övrig information2: jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 950

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.120 mm

Invändig diameter: 1.000 mm

Total höjd: 3.350 mm

Ytterdiameter: 1.250 mm

**Omrörare**

Kraft (kW): 1,50  
Varvtal: 20 - 120

**Mer**

Värmeväxlare: RVS 304  
Isolerad: Ja