956 liter tank i Syrafast 316



219 000 SEK /st exkl moms

Additional information: Technical documentation (also for the agitator) available for one of the two vessels
Volumetric volume (L): 956 L
Pressure in tank: pressure and vacuum
Min. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 83 L
Max Overpressure: 1,50 Bar
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25

Agitator: yes
Number of revolutions: 24 - 247
Cylinder: 5 mm
Bottom: 5 mm
Internal diameter tank: 1.000 mm

Outer diameter tank: 1.050 mm
Cylinder height: 950 mm
Total height of tank: 2.000 mm

SKU: 489937

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Pharmacy; Technical documentation (also for the agitator) available for one of the two vessels; we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Undertryck (vakuum): 0,50 Bar
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 956

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 950 mm
Invändig diameter: 1.000 mm
Total höjd: 2.000 mm
Ytterdiameter: 1.050 mm

Omrörare
Varvtal: 24 – 247

Tjocklek på tank
Botten: 5 mm
Cylinder: 5 mm

Mer
Isolerad: Nej