

9670 liter tank i Rostfritt 304



345,000,00 kr /st exkl moms

Additional information: Chemistry; 4 support brackets, Fe; external parts of the manhole cover partly made of Fe; 1 Half coil heater connection cut off (see photos); some residues of previous content

Volumetric volume (L): 9.670 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 200 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN100

Agitator: yes

Number of revolutions: 256

Power: 7,50

Top: 8 mm

Cylinder: 8 mm

Bottom: 6 mm

Internal diameter tank: 2.000 mm

Cylinder height: 2.500 mm

Total height of tank: 4.900 mm

SKU: 300872

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets, Fe; external parts of the manhole cover partly made of Fe; 1 Half coil heater connection cut off (see photos); some residues of previous content; we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 9670

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.500 mm

Invändig diameter: 2.000 mm

Total höjd: 4.900 mm

Omrörare

Kraft (kW): 7,50

Varvtal: 256

Tjocklek på tank

Botten: 6 mm

Cylinder: 8 mm

Topp: 8 mm

Mer

Isolerad: Nej