

985 liter tank i Syrafast 316



119 000 SEK /st exkl moms

Additional information: Pharmacy; Vessel is part of a pharmaceutical plant in a frame, Aisi 304; overall dimensions in the frame are partly estimated and may vary slightly

Volumetric volume (L): 985 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 82 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Power: 0,55

Internal diameter tank: 880 mm

Outer diameter tank: 1.000 mm

Total height of tank: 2.950 mm

Total outer width: 1.400 mm

Total outer length: 3.000 mm

SKU: 440720

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; Vessel is part of a pharmaceutical plant in a frame, Aisi 304; overall dimensions in the frame are partly estimated and may vary slightly; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 985

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 880 mm

Total höjd: 2.950 mm

Ytterdiameter: 1.000 mm

Omrörare

Kraft (kW): 0,55

Mer

Isolerad: Ja