3500 liter tank i Syrafast 316



81 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 3 support brackets, Aisi 304; further technical documents available; different design of the manholes (see photos)
Volumetric volume (L): 3.500 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN50
Top: 7 mm

Cylinder: 6 mm
Bottom: 5,10 mm
Internal diameter tank: 1.600 mm
Cylinder height: 1.300 mm
Total height of tank: 2.300 mm

Empty weight tank: 770

SKU: 406505

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry; 3 support brackets, Aisi 304; further technical documents available; different design of the manholes (see photos)
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.300 mm
Invändig diameter: 1.600 mm
Total höjd: 2.300 mm

Tjocklek på tank
Botten: 5,10 mm
Cylinder: 6 mm
Topp: 7 mm

Mer
Isolerad: Nej
Vikt: 770

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se