

1356 liter tank i Syrafast 316



86,000,00 kr /st exkl moms

Additional information: Pharmaceutical chemistry; 3 feet, Aisi 304 screwed to support brackets, Aisi 304; 1 longitudinal sight glass each in the cylinder and in the lower bottom; on the outlet there is a fitting with a pipe diameter of approx. 38 mm inside; manhole cover is missing

Volumetric volume (L): 1.356 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 26 - 156

Power: 2,50

Top: 8,80 mm

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 1.200 mm

Cylinder height: 900 mm

Total height of tank: 3.250 mm

SKU: 282514

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 3 feet, Aisi 304 screwed to support brackets, Aisi 304; 1 longitudinal sight glass each in the cylinder and in the lower bottom; on the outlet there is a fitting with a

Övrig information2: pipe diameter of approx. 38 mm inside ; manhole cover is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1356



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 900 mm
Invändig diameter: 1.200 mm
Total höjd: 3.250 mm

Omrörare

Kraft (kW): 2,50
Varvtal: 26 - 156

Tjocklek på tank

Botten: 5 mm
Cylinder: 5 mm
Topp: 8,80 mm

Mer

Isolerad: Nej