

## 1356 liter tank i Syrafast 316



## 86 000 SEK /st exkl moms

**Additional information:** Pharmaceutical chemistry; 3 feet, stainless steel 304 screwed to stainless steel 304 brackets; 1 longitudinal sight glass in the cylinder and 1 in the base; there is a fitting on the spout, inner tube diameter approx. 38 mm; manhole cover is missing

**Volumetric volume (L):** 1.356 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 2 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** flange DN80

**Agitator:** yes

**Number of revolutions:** 26 - 156

**Power:** 2,50

**Top:** 8,80 mm

**Cylinder:** 5 mm

**Bottom:** 5 mm

**Internal diameter tank:** 1.200 mm

**Cylinder height:** 900 mm

**Total height of tank:** 3.250 mm

**SKU:** 282514

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 3 feet, Aisi 304 screwed to support brackets, Aisi 304; 1 longitudinal sight glass each in the cylinder and in the lower bottom; on the outlet there is a fitting with a

Övrig information2: pipe diameter of approx. 38 mm inside ; manhole cover is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1356



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 900 mm  
Invändig diameter: 1.200 mm  
Total höjd: 3.250 mm

## Omrörare

Kraft (kW): 2,50  
Varvtal: 26 - 156

## Tjocklek på tank

Botten: 5 mm  
Cylinder: 5 mm  
Topp: 8,80 mm

## Mer

Isolerad: Nej