

## 1830 liter tank i Syrafast 316



## 196 000 SEK /st exkl moms

**Additional information:** Pharmaceutical chemistry; Half-coil, Aisi 304 in the lower cylinder area; hand hole diameter approx. 200 mm; 1 slightly larger and several small dents in the insulation jacket; Outlet fitting incomplete; some residues of previous content

**Volumetric volume (L):** 1.830 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 26 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 50 - 500

**Power:** 0,75

**Cylinder:** 5 mm

**Bottom:** 5,40 mm

**Internal diameter tank:** 1.200 mm

**Outer diameter tank:** 1.460 mm

**Cylinder height:** 1.287 mm

**Total height of tank:** 2.650 mm

**SKU:** 281053

---

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Half-coil, Aisi 304 in the lower cylinder area; hand hole diameter approx. 200 mm; 1 slightly larger and several small dents in the insulation jacket;

Outlet fitting

Övrig information2: incomplete; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1830

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 1.287 mm  
Invändig diameter: 1.200 mm  
Total höjd: 2.650 mm  
Ytterdiameter: 1.460 mm

## Omrörare

Kraft (kW): 0,75  
Varvtal: 50 - 500

## Tjocklek på tank

Botten: 5,40 mm  
Cylinder: 5 mm

## Mer

Isolerad: Ja