

1830 liter tank i Syrafast 316



199,000,00 kr /st exkl moms

Additional information: Pharmaceutical chemistry; Half-coil, Aisi 304 in the lower cylinder area; hand hole diameter approx. 200 mm; 1 slightly larger and several small dents in the insulation jacket; Outlet fitting incomplete; some residues of previous content

Volumetric volume (L): 1.830 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 26 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 50 - 500

Power: 0,75

Cylinder: 5 mm

Bottom: 5,40 mm

Internal diameter tank: 1.200 mm

Outer diameter tank: 1.460 mm

Cylinder height: 1.287 mm

Total height of tank: 2.650 mm

SKU: 281053

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Half-coil, Aisi 304 in the lower cylinder area; hand hole diameter approx. 200 mm; 1 slightly larger and several small dents in the insulation jacket;

Outlet fitting

Övrig information2: incomplete; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1830

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.287 mm
Invändig diameter: 1.200 mm
Total höjd: 2.650 mm
Ytterdiameter: 1.460 mm

Omrörare

Kraft (kW): 0,75
Varvtal: 50 - 500

Tjocklek på tank

Botten: 5,40 mm
Cylinder: 5 mm

Mer

Isolerad: Ja