

730 liter tank i Syrafast 316



171 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Half-coil for heating/cooling around the lower cylindrical area and the lower bottom; hand hole diameter 150 mm; outlet fitting incomplete; Device for load cells under the feet (probably 3 load cells available; loose load cells were not taken into account when specifying the total height), insulation jacket partially cut open in the area of the lower bottom; Technical

documents are available from the manufacturer and could be purchased directly from the manufacturer if required; bump at the insulation jacket; handhole cover is missing

Volumetric volume (L): 730 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 12 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 53

Agitator: yes

Number of revolutions: 270

Power: 1,50

Internal diameter tank: 790 mm

Outer diameter tank: 1.080 mm

Cylinder height: 1.200 mm

Total height of tank: 2.950 mm

Empty weight tank: 700

SKU: 281158

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Half-coil for heating/cooling around the lower cylindrical area and the lower bottom; hand hole diameter 150 mm; outlet fitting incomplete;

Device for load cells under the

Övrig information2:

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 730

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.200 mm

Invändig diameter: 790 mm

Total höjd: 2.950 mm

Ytterdiameter: 1.080 mm

Omrörare

Kraft (kW): 1,50

Varvtal: 270

Mer

Isolerad: Ja

Vikt: 700