

## 2420 liter tank i Syrafast 316



**230,000,00 kr /st exkl moms**

**Additional information:** Pharmaceutical chemistry; Manhole DN 350/450 (manhole cover incomplete); Support ring, Fe; Flanges partially Fe

**Volumetric volume (L):** 2.420 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 100 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** 130

**Agitator:** yes

**Number of revolutions:** 8.2 - 41

**Power:** 7,50

**Top:** 7 mm

**Cylinder:** 6 mm

**Bottom:** 6,10 mm

**Internal diameter tank:** 1.400 mm

**Cylinder height:** 1.180 mm

**Total height of tank:** 3.950 mm

**SKU:** 281206

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Manhole DN 350/450 (manhole cover incomplete); Support ring, Fe; Flanges partially Fe; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2420

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.180 mm  
Invändig diameter: 1.400 mm  
Total höjd: 3.950 mm

## Omrörare

Kraft (kW): 7,50  
Varvtal: 8.2 - 41

## Tjocklek på tank

Botten: 6,10 mm  
Cylinder: 6 mm  
Topp: 7 mm

## Mer

Isolerad: Nej