

3690 liter tank i Syrafast 316



255 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Manhole cover incomplete (e.g. the sight glass is missing, see photos); support ring made of Fe

Volumetric volume (L): 3.690 L

Pressure in tank: vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 145 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 130

Agitator: yes

Number of revolutions: 6 - 32

Power: 11

Top: 7,90 mm

Cylinder: 6 mm

Bottom: 6,50 mm

Internal diameter tank: 1.600 mm

Cylinder height: 1.380 mm

Total height of tank: 4.350 mm

SKU: 281236

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Manhole cover incomplete (among other things, the sight glass is missing, see photos); Support ring made of Fe; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3690

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.380 mm
Invändig diameter: 1.600 mm
Total höjd: 4.350 mm

Omrörare

Kraft (kW): 11
Varvtal: 6 – 32

Tjocklek på tank

Botten: 6,50 mm
Cylinder: 6 mm
Topp: 7,90 mm

Mer

Isolerad: Nej