

## 3586 liter tank i Syrafast 316



## 253,000,00 kr /st exkl moms

**Additional information:** Pharmaceutical chemistry; Sight glasses in the manhole covers are missing; support ring, Fe; Flanges partly made of Fe

**Volumetric volume (L):** 3.586 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 202 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 130

**Agitator:** yes

**Number of revolutions:** 30-184

**Power:** 6,80

**Top:** 9,10 mm

**Cylinder:** 6 mm

**Bottom:** 6,50 mm

**Internal diameter tank:** 1.600 mm

**Cylinder height:** 1.377 mm

**Total height of tank:** 3.750 mm

**SKU:** 281938

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Sight glasses in the manhole covers are missing; support ring, Fe; Flanges partly made of Fe; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3586



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.377 mm  
Invändig diameter: 1.600 mm  
Total höjd: 3.750 mm

## Omrörare

Kraft (kW): 6,80  
Varvtal: 30-184

## Tjocklek på tank

Botten: 6,50 mm  
Cylinder: 6 mm  
Topp: 9,10 mm

## Mer

Isolerad: Nej