

## 2330 liter tank i Syrafast 316



**95 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical chemistry; Double jacket made of stainless steel 304 around the lower cylinder area and the lower base; 3 stainless steel claws; parts of the insulating collar were cut off during disassembly; bump at the insulation jacket

**Volumetric volume (L):** 2.330 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 165 L

**Max Overpressure:** 2 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** flange DN50

**Top:** 7 mm

**Cylinder:** 6 mm

**Bottom:** 5,80 mm

**Internal diameter tank:** 1.400 mm

**Outer diameter tank:** 1.650 mm

**Cylinder height:** 1.130 mm

**Total height of tank:** 2.150 mm

**SKU:** 282094

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Double jacket made of stainless steel 304 around the lower cylinder area and the lower base; 3 stainless steel claws; parts of the insulating collar were cut off during

Övrig information2: disassembly; bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2330

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.130 mm

Invändig diameter: 1.400 mm

Total höjd: 2.150 mm

Ytterdiameter: 1.650 mm

## Tjocklek på tank

Botten: 5,80 mm

Cylinder: 6 mm

Topp: 7 mm

## Mer

Värmeväxlare: RVS 304

Isolerad: Ja