

2330 liter tank i Syrafast 316



94,000,00 kr /st exkl moms

Additional information: Pharmaceutical chemistry; Double jacket made of stainless steel 304 around the lower cylinder area and the lower base; 3 stainless steel claws; parts of the insulating collar were cut off during disassembly; bump at the insulation jacket

Volumetric volume (L): 2.330 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 165 L

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN50

Top: 7 mm

Cylinder: 6 mm

Bottom: 5,80 mm

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.650 mm

Cylinder height: 1.130 mm

Total height of tank: 2.150 mm

SKU: 282094

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Double jacket made of stainless steel 304 around the lower cylinder area and the lower base; 3 stainless steel claws; parts of the insulating collar were cut off during

Övrig information2: disassembly; bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2330

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.130 mm

Invändig diameter: 1.400 mm

Total höjd: 2.150 mm

Ytterdiameter: 1.650 mm

Tjocklek på tank

Botten: 5,80 mm

Cylinder: 6 mm

Topp: 7 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja