

## 3860 liter tank i Syrafast 316



**255 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical chemistry; Support ring, Fe; manhole cover incomplete (see photos); bump at the insulation jacket; manhole cover plated

**Volumetric volume (L):** 3.860 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 136 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 61

**Power:** 4

**Top:** 8,14 mm

**Cylinder:** 6 mm

**Bottom:** 5,17 mm

**Internal diameter tank:** 1.800 mm

**Outer diameter tank:** 2.090 mm

**Total height of tank:** 3.050 mm

**SKU:** 282610

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; Support ring, Fe; Manhole cover incomplete (see photos); bump at the insulation jacket;manhole cover plated; we can't give any guarantees about the heating/cooling

Övrig information2: jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3860

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Invändig diameter: 1.800 mm

Total höjd: 3.050 mm

Ytterdiameter: 2.090 mm

## Omrörare

Kraft (kW): 4

Varvtal: 61

## Tjocklek på tank

Botten: 5,17 mm

Cylinder: 6 mm

Topp: 8,14 mm

## Mer

Isolerad: Ja