

## 500 liter tank i Syrafast 316



**225,000,00 kr /st exkl moms**

**Additional information:** Tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 220mm; incl. Södmo single-seat valve SVP (outlet)

**Volumetric volume (L):** 500 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 28 L

**Max Overpressure:** 10 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available



**Top:** 4 mm

**Cylinder:** 6 mm

**Bottom:** 3,50 mm

**Internal diameter tank:** 800 mm

**Outer diameter tank:** 980 mm

**Cylinder height:** 1.044 mm

**Empty weight tank:** 600

**SKU:** 440882

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 220mm; incl. Südmo single-seat valve SVP (outlet); we can't give any

Övrig information2: guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 500

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.044 mm

Invändig diameter: 800 mm

Ytterdiameter: 980 mm

**Tjocklek på tank**

Botten: 3,50 mm

Cylinder: 6 mm

Topp: 4 mm

**Mer**

Isolerad: Ja

Vikt: 600